

WIND

Wind Transmitter "First Class" Advanced X

Part number: 4.3352.00.4xx

The wind transmitter is designed for the acquisition of the horizontal component of the wind velocity in the field of meteorology and environmental measuring technology, evaluation of location, and measurement of capacity characteristics of wind power systems. In the plain country the wind transmitter meets all requirements of IEC 61400-12-1 Edition 2.0 for an Instrument of the accuracy class 0.65.

Special characters are a defined and optimised, dynamic behaviour also at high turbulence intensity, minimal over-speeding, and a low starting value.

The measuring value is available at the output as digital signal and via RS485 interface. It can be transmitted to display instruments, recording instruments, data loggers as well as to process control systems. The serial interface supports the THIES- ASCII and the MODBUS RTU- format.

For winter operation the instrument (4.3352.00.400) is equipped with an electronically regulated heating, which guarantees a smooth running of the ball bearings, and prevents the shaft and slot from icing-up.



Specification

Part number: 4.3352.00.4xx

Wind speed	
Measuring range	0 ... 75 m/s
Accuracy	< 1 % of meas. value (0.3 ... 50 m/s) or < ±0.2 m/s
Linearity	r > 0.99999 (4 ... 20 m/s)
Inclined flow	< 0.1% (mean deviation from cosinus line at 12 m/s ; ±20 °)
Delay distance	< 3 m (aac. to ASTM D 5096-96)
Air pressure	
Measuring range	300 ... 1100 hPa
Accuracy	±1 hPa @ 20 °C
Indication	
Measuring range	-89.9 ... +89.9 °
Accuracy	±1 °
Measuring axis	X, Y, Z
Vibration	
Measuring range	0 ... 50 Hz
Accuracy	±0.4 Hz
Measuring axis	X, Y, Z
Acceleration	
Measuring range	±8 g
Accuracy	±30 mg
Data output digital	

Interface	RS485
Baudrate	1200 ... 57600 Baud
Duplex mode	Half duplex
Protocol	ASCII / MODBUS
Frequency	1082 Hz @ 50 m/s
Operating voltage	
Electronic	3.7 ... 42 V DC 40 mA typ. 100 mA max.
Heating	24 V AC/DC, max 25 W
General	
Ambient temp.	-50 ... +80 °C
Electr. connection	8 pol. plug connection
Mounting	onto mast tube Ø 1''
Protection	IP 55
Survival speed	80 m/s (min. 30 minutes)
Weight	0.5 kg
Fixing boring	Ø 35 x 25 mm
Material housing	aluminium, anodised
Material cup star	carbon-fiber glass reinforced

Versions

As per 4.3352.00.4xx, but:

Product number 4.3352.00.400

Data output digital

Protocol	THIES - ASCII
----------	---------------



Product number 4.3352.00.401

Data output digital

Protocol	MODBUS - RTU
----------	--------------

Accessories

Product	Product name	Brief description
---------	--------------	-------------------

	<p>Traverse for Wind Transmitters "First Class" 4.3174.00.000</p>	<p>For mounting the wind speed transmitter and wind direction transmitter jointly onto a mast.</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Height</td> <td>0.76 m</td> </tr> <tr> <td>Mounting</td> <td>on mast tube Ø 1,5"</td> </tr> <tr> <td>Material</td> <td>aluminium, anodised (AlMgSi0.5)</td> </tr> <tr> <td>Sensor distance horizontal</td> <td>0.6 m</td> </tr> <tr> <td>Sensor distance vertikal</td> <td>0.2 m</td> </tr> <tr> <td>Weight</td> <td>3 kg</td> </tr> <tr> <td>Fixing boring</td> <td>Ø 34 mm for First Class wind sensors</td> </tr> </table>	General		Height	0.76 m	Mounting	on mast tube Ø 1,5"	Material	aluminium, anodised (AlMgSi0.5)	Sensor distance horizontal	0.6 m	Sensor distance vertikal	0.2 m	Weight	3 kg	Fixing boring	Ø 34 mm for First Class wind sensors
General																		
Height	0.76 m																	
Mounting	on mast tube Ø 1,5"																	
Material	aluminium, anodised (AlMgSi0.5)																	
Sensor distance horizontal	0.6 m																	
Sensor distance vertikal	0.2 m																	
Weight	3 kg																	
Fixing boring	Ø 34 mm for First Class wind sensors																	
	<p>Hanger 1m First Class 4.3184.01.000</p>	<p>The hanger is used for the lateral mounting of a wind transmitter, First Class type, onto a mast</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Length</td> <td>1 m</td> </tr> <tr> <td>Mounting</td> <td>at mast tube Ø 40 ... 80 mm</td> </tr> <tr> <td>Material</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Weight</td> <td>1.5 kg</td> </tr> <tr> <td>Fixing boring</td> <td>Ø 34 mm</td> </tr> </table>	General		Length	1 m	Mounting	at mast tube Ø 40 ... 80 mm	Material	aluminium (AlMgSi0.5)	Weight	1.5 kg	Fixing boring	Ø 34 mm				
General																		
Length	1 m																	
Mounting	at mast tube Ø 40 ... 80 mm																	
Material	aluminium (AlMgSi0.5)																	
Weight	1.5 kg																	
Fixing boring	Ø 34 mm																	

